





High Power

- Long wheelbase with large breakout force and traction force
- Cummins 6CTA8-3-C215 Turbo engine 164kw
- Reinforced drive system
- ZF Transmission

Comfort & Convenience

- Cab space enlarged by 15%
- Low noise, shock-absorbed and dust-proof cab
- Rear opening engine hood, for easy maintenance
- Pilot control Joystick
- High volume air conditioned pressurised cabin
- Automatic bucket levelling

Reliability & Durability

- Upgraded hydraulic system
- New design electrical system
- · Optimal designed structural components

HEAVY

Safety

CONSTRUCTION SERIES

- ROPS & FOPS cab
- External self cleaning disk braking system
- Luxurious operating environment

Energy Saving & Green Initiative

- Low fuel and energy consumption
- Low noise

WWW.OLYMPUSLOADERS.COM.AU



YX657HD

ARTICULATED WHEEL LOADERS





SPECIFICATIONS

 Overall Weight
 17250kg

 LxWxH (mm)
 7930 x 3020 x 3420

 Rated Bucket capacity (m3)
 3-4.5

Rated Bucket capacity (m3) 3-4.5
Rated Load (kg) 5000
Max. Dump Height (mm) 3300
Bucket Indicator Yes

ENGINE

Model 6CTA8-3-C215
Type Vertical Inline,
Water Cooling
Four Stroke
Turbo Diesel

Rated Power (kw) 164kw Rated Speed (r/min) 2400

TRANSMISSION SYSTEM

Model ZF Transmission
Gearbox Type Electronic Powershift
Gear Shift 4 Forward, 3 Reverse

MAIN HYDRAULIC SYSTEM

Working Pressure 18mpa Boom Lifting Time 4.8sec Fuel Tank Capacity 300Lt

STEERING SYSTEM

Type Load Sensing
Hydraulic Steering
Min Turn Radius (mm) 6030

TYRES

Standard Tyres 23.5/70-25

STANDARD BUCKET

Width (mm) 3100

ROPS CERTIFIED CABIN

With its high volume Air Conditioner upgrade we have created a much better cooling system for Australia, combined with a sealed cabin it eliminates noise and dust from its working conditions. The sealed cabin has a AM/FM stereo, reversing camera, external fan, suspension seat and tilting steering wheel with warning lights for engine and transmission management.

MODERN CONTROLS

The YX657 Olympus series model has electronic gear change and also the auxilliary hydraulic function can be operated from push buttons on the joystick as an option. On the dash there is bucket float control activation and all the switches for lights, windscreen washer and accessories, etc. The electronic pilot control joy stick is smooth and light to operate giving a sensitive feeling to the operation of the loaders bucket. Auto bucket leveling is also standard. A large rear vision camera is fitted inside the cab for safe, easy reversing.

BRAKING SYSTEM

Olympus models run a dry brake system combining air over hydraulic disc brakes. The disc brakes are self cleaning and are easy maintained with debris covers for protection. Air operated hand brakes are standard in all models and are located next to the operator's seat.

MULTI PURPOSE TOOL HANDLING

Hydraulic hitches are able to quickly change attachments; from bucket to hayspears to pallet forks within a few seconds. This is achieved from an auxiliary hydraulic function also able to run hydraulic attachments i.e., augers, 4in1 buckets, hydraulic forks etc.



Olympus Equipment Sales

E: sales@olympusloaders.com.au P: Simon - 0427 744 049 2/25-29 Riverland Drive Loganholme Q 4129